



# SAFETY DATA SHEET

## 1. IDENTIFICATION OF THE PRODUCT AND MANUFACTURER

### VERTICAL JOINT PROFILER (VOC) IN-FORM RETARDERS

**Manufacturer Name & Address:**

Arcal Chemicals, Inc.  
223 West Hampton Avenue  
Capitol Heights, MD 20743

**General Information:**

(Tel) 301-336-9300  
(Fax) 301-336-6597

**Emergency CHEMTREC:**

In case of chemical emergencies  
800-424-9300 (within USA)  
703-527-3887 (outside of USA)

## 2. HAZARDS IDENTIFICATION



Vertical Joint Profiler retarders are liquids that contain flammable solvents. Their flash point is 45° F and they can burn if set afire; the dried film will not burn easily. The vapor is heavier than air and can drift to low points in the area. Empty containers may still contain hazardous residue or vapor. Eye contact will cause irritation. Prolonged skin contact can cause irritation by removing natural skin oils. Inhalation of the vapors may cause headache or dizziness. Ingestion is highly unlikely. They do not contain known carcinogens.

## 3. COMPOSITION AND INFORMATION ON INGREDIENTS

<u>Hazardous Component</u>	<u>CAS #</u>	<u>Conc.</u>	<u>OSHA PEL</u>	<u>ACGIH TWA</u>
t-butyl acetate	540-88-5	27-31%	NA	NA

## 4. FIRST AID MEASURES

**Eye contact:** Flush with clean water for 15 minutes or until irritation subsides. If irritation persists, seek medical advice.

**Inhalation:** Move the exposed person to fresh air. Administer oxygen or begin resuscitation if necessary.

**Skin contact:** Remove contaminated clothing and use a mild solvent like mineral spirits to clean skin, then wash with soap and water.

**Ingestion:** In case of this unlikely event, do not induce vomiting (to avoid getting material into the lungs) and obtain medical help immediately.

---

## 5. FIRE-FIGHTING MEASURES

### NFPA FIRE HAZARDS:

**HEALTH**  
1 (slight)

**FLAMMABILITY**  
3 (high)

**REACTIVITY**  
0 (insignificant)

Prevent vapor concentrations and avoid flash fires by use of adequate ventilation. In case of fire, use water spray, foam or dry chemical to control small fires. Avoid boil over by not spraying water directly into containers. Burning material will produce carbon oxides (monoxide and dioxide). Protect personnel from heat, flame and vapors which may travel.

---

## 6. ACCIDENTAL RELEASE MEASURES

In case Vertical Joint Profiler retarder is spilled, treat with absorbent material like vermiculite, kitty litter or sand, scoop up and dispose with hazardous waste. Keep away from all sources of ignition, heat or flame while the waste still contains solvent.

---

## 7. HANDLING AND STORAGE

Store Vertical Joint Profiler retarder in a cool dry place where rain will not collect on pails and where heat from equipment or the sun will not expose the product to temperature extremes.

---

## 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Where ventilation is insufficient to insure low personal exposure, see Section 3 for Permissible Exposure Limit (PEL) and Time Weighted Average (TWA) and use appropriate monitoring equipment. Splash-proof safety goggles and chemically resistant gloves (without tears, pinholes or other signs of wear) are highly recommended to protect personnel.

---

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**Appearance:** Paint-like liquid; color varies with etch grade

**Odor:** Solvent

**Density:** 9-10 pounds per gallon

**Boiling point:** 185F - 230F

**Volatile Organic Content:** (VOC Exempt): <6 g/L

**Solubility in water:** Insoluble

**Flash point:** 45° F estimated

---

## 10. STABILITY AND REACTIVITY

Vertical Joint Profiler retarders are not subject to runaway polymerization. Avoid contact with strong oxidizing agents like nitric acid, and with any strong acids, which can generate foam. The major hazard is flammability, so store material away from sources of ignition and do not allow fire or flame near the liquid product.

---

---

## 11. TOXICOLOGICAL INFORMATION

The primary irritant effect of ACC retarders is by way of the solvents on the eye and on the skin. The individual ingredients are diluted and contained in a semisolid film when the product is dried, and the complete product has not been tested.

---

## 12. ECOLOGICAL INFORMATION

Do not allow liquid product to reach ground water, water course or sewer. Although the product is insoluble in water, odor and taste of the water can be affected.

---

## 13. DISPOSAL CONSIDERATIONS

Waste product is hazardous (US EPA: due to ignitability). Do not dispose with residential garbage or allow product to reach ground water or sewer.

---

## 14. TRANSPORT INFORMATION *(applies to all modes of transport)*

<b>ID No.</b>	<b>Proper Shipping Name</b>	<b>Hazardous Class</b>	<b>Packing Group</b>
UN 1263	Paint Related Material	3	II

---

## 15. REGULATORY INFORMATION

TSCA: All ingredients are listed.

---

## 16. OTHER INFORMATION

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances.